

Specifications — IPL T PCS4, IPL T PCS4i

Ethernet control interface

| | |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Connectors | 1 RJ-45 female connector |
| Data rate | 10/100Base-T, half/full duplex with autotdetect |
| Protocols | ARP, DHCP, ICMP (ping), TCP/IP, UDP/IP, Telnet, HTTP, SMTP |
| Default settings | Link speed and duplex level = autotdetected IP address = 192.168.254.254 Subnet mask = 255.255.0.0 Gateway = 0.0.0.0 DHCP = off |
| Web server | Up to 200 simultaneous sessions 960 kB nonvolatile user memory |
| Program control | Extron's Simple Instruction Set (SIS™) |
| Global Viewer requirements | Microsoft® Internet Explorer ver. 6 or higher |

AC control interface

| | |
|-----------------------------|-------------------------------------------------------------------------------------------------------|
| Connectors | |
| IPL T PCS4 | 4 USA/Edison power connectors |
| IPL T PCS4i | 4 IEC power connectors |
| Voltage | |
| IPL T PCS4 | 120 VAC, 50-60 Hz |
| IPL T PCS4i | 220 VAC, 50-60 Hz |
| Minimum AC load | |
| IPL T PCS4 | 20 mA, 2.4 watts at 120 VAC |
| IPL T PCS4i | 20 mA, 4.4 watts at 220 VAC |
| Maximum AC load, aggregate | |
| IPL T PCS4 | 10 A, 1200 watts at 120 VAC |
| IPL T PCS4i | 10 A, 2200 watts at 220 VAC |
| Maximum AC load, individual | |
| IPL T PCS4 | 10 A, 1200 watts at 120 VAC |
| IPL T PCS4i | 10 A, 2200 watts at 220 VAC |
| Current sense | |
| Range | 5 mA to 10 A |
| Resolution | 0.1 mA steps from 5 mA to 99.9 mA 1 mA steps from 100 mA to 999 mA 10 mA steps from 1 A to 10 A |
| Tolerance | ±20% |

Alarm relay control

| | |
|----------------------|--------------------------------------------|
| Quantity/type | 1 normally open relay |
| Connector | (1) 3.5 mm captive screw connector, 2 pole |
| Contact rating | 24 V, 1 A |

General

| | |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Power input | |
| PL T PCS4 | 120 VAC, 50/60 Hz, 15 watts, internal |
| IPL T PCS4i | 220 VAC, 50/60 Hz, 15 watts, internal |
| Temperature/humidity | Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing |
| Rack mount | Yes, with optional 1U 9.5" deep rack shelf kit, part #60-190-01 Also under-furniture mountable with optional bracket kit, part #70-077-01. |
| Enclosure type | Metal |
| Enclosure dimensions | 1.7" H x 8.7" W x 9.5" D (1U high, half rack wide) 4.3 cm H x 22.0 cm W x 24.1 cm D (Depth excludes connectors.) |

| | |
|-----------------------|--------------------------------------------------------------------------------------|
| Product weight | 2.6 lbs (1.2 kg) |
| Shipping weight | 5 lbs (3 kg) |
| Vibration | ISTA 1A in carton (International Safe Transit Association) |
| Listings | UL, CUL |
| | UL rated for use in a plenum air space: meets UL2043 and UL60950 for fire and smoke. |
| Compliances | CE, FCC Class A, VCCI, AS/NZS, ICES |
| MTBF | 30,000 hours |
| Warranty | 3 years parts and labor |

NOTE *All nominal levels are at $\pm 10\%$*

NOTE *Specifications are subject to change without notice.*

(7.51-020106-D7)